

VOLUME I
SUMMARY AND CONCLUSIONS

Report On
ENGINEERING WATER CODE STUDIES FOR THE SOUTH PLATTE RIVER
Under Authorization of Senate Bill 407
46th Colorado General Assembly

Morton W. Bittinger & Assoc.
and
Wright Water Engineers
August, 1968

Morton W. Bittinger & Associates
Water Resources Engineers
P. O. Box 1592
Fort Collins, Colorado

Wright Water Engineers
Engineering Consultants
1240 West Bayaud Avenue
Denver, Colorado

August 29, 1968

Mr. James D. Geissinger
Attorney at Law
Equitable Building
Denver, Colorado 80202

Dear Mr. Geissinger:

We are pleased to submit herewith our summary report on "Engineering Water Code Studies for the South Platte River." This report contains conclusions and recommendations derived from individual area studies performed under authorization of Senate Bill 407 passed by the 46th General Assembly.

We sincerely appreciate the opportunity to participate in this very important work for the State of Colorado. Our studies have confirmed that it is highly desirable to implement planned utilization of our valuable groundwater resources and reservoirs in conjunction with surface water supplies and facilities. Formulation of legislation which will allow and encourage the integrated management, administration and use of surface water and groundwater, without infringement of present vested rights, will require considerable ingenuity on the part of the attorneys and legislators involved. We hope that this formulation will continue with the optimism, open-mindedness and advanced thinking that you, Mr. Eckles, Mr. Sparks and others have evidenced to date.

It is also important that the water users fully understand the legislation as finally proposed, the reasoning behind it and the alternatives. We believe that considerable thought and effort should go into a public information program prior to consideration of the proposed legislation by the General Assembly.

Sincerely yours,

Morton W. Bittinger

Morton W. Bittinger

Kenneth R. Wright

Kenneth R. Wright

Report On
ENGINEERING WATER CODE STUDIES FOR THE SOUTH PLATTE RIVER
Under Authorization of Senate Bill 407
46th Colorado General Assembly

Morton W. Bittinger & Assoc.
and
Wright Water Engineers
August, 1968

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION.	1
Background	1
Scope of this report	1
Basic premises	2
GENERAL SUMMARY OF SOUTH PLATTE STUDIES	3
Findings	3
Conclusions.	4
Recommendations.	4
SPECIFIC CONCLUSIONS.	5
Water District 64.	5
Water District 8	6
Water District 1	9
Water District 2	10
Water Districts 3, 4, 5, and 6	12
APPENDIX.	15
Water District 64, Table of Contents	16
Water District 64, List of Tables and Figures.	17
Water District 8, Table of Contents.	18
Water District 8, List of Tables	19
Water District 8, List of Figures.	21
Water District 1, Table of Contents.	22
Water District 1, List of Figures.	24
Water District 1, List of Tables	25
Water District 2, Table of Contents.	26
Water District 2, List of Tables	27
Data Appendix A, Table of Contents.	28
Data Appendix B, Volume I, Table of Contents.	29
Data Appendix B, Volume II, Table of Contents	30
Data Appendix B, Volume III, Table of Contents.	31

(Only a limited number of copies of the data appendices were printed. These are available for inspection at the office of the State Engineer)

INTRODUCTION

Background

Senate Bill 407 of the 46th session of the Colorado General Assembly authorized the Coordinator of Natural Resources to undertake a study leading to recommendations for legislation which would provide for the integrated use of ground and surface water and to a fuller utilization of the waters of the State.

In this undertaking he was authorized to call upon private engineers to work in cooperation with the Colorado Water Conservation Board staff. The initial assignments by the Coordinator of Natural Resources were made in August of 1967 and completed on January 1, 1968. Subsequent assignments were made in April of 1968 by Mr. James Geissinger, attorney at law, who is under contract to the Coordinator of Natural Resources.

The initial assignments were as follows:

Platte River Basin

1. Wright Water Engineers, Water District 64, Balzac to Julesburg at the State line.
2. Bittinger and Associates, Water District No. 1, Kersey to Balzac.
3. Colorado Water Conservation Board, Water District No. 2, Clear Creek to Kersey.

Arkansas River Basin

1. W. W. Wheeler and Associates and Woodward-Clyde and Associates.

In April of 1968, additional assignments were as follows:

1. Bittinger and Associates, Water Districts No. 2, 3, 4, 5, and 6, South Platte River from Denver to Kersey, the Cache la Poudre River, the Big Thompson River, St. Vrain Creek and Boulder Creek.
2. Wright Water Engineers, Water District No. 8, South Platte River from Denver to South Platte.
3. W. W. Wheeler and Associates and Woodward-Clyde and Associates, continuation of studies on the Arkansas River.

Scope of this report

This report is a summary of the conclusions contained in the reports on Water Districts 64, 1, 2, and 8 plus general conclusions from studies of Water Districts 3, 4, 5, and 6, all within the South Platte River Basin. Pertinent data has been abstracted from the separate reports. The Table of Contents, List of Figures, and List of Tables for each of the separate reports have been included in the Appendix for reference.

Basic Premises

The problem at hand is complex and controversial from many standpoints--physical (hydraulic interrelationships), legal (protection of vested rights), customs (water-use practices), organizations and individuals (overlapping and competing), administration (multitude of points of diversion), etc. It is desirable, therefore, that a few basic premises which have been established be stated:

1. That it is in the best interest of the State of Colorado and its water users to develop legislation which (a) will promote and allow an increasingly greater beneficial use of the total water supply, (b) will increase the dependability of supplies available to water users, and (c) will alleviate conflicts between water users.

2. That shutting off of wells to satisfy senior surface rights is a negative approach which does not allow utilization of a reserve of stored water when it is most needed. Thus, if senior rights can be served by other means, generalized shutting down of wells in areas such as that under study is not in the best interest of the State of Colorado and its water users.

3. That (a) greater beneficial use, (b) better dependability of supply, and (c) a mitigation of conflicts between water users can be attained through planned integrated management and use of surface water and groundwater in the area of study. Such integrated management not only includes the planned utilization of groundwater, but also the planned manipulation of groundwater storage in conjunction with surface water storage and conveyance facilities.

4. That the science of groundwater hydraulics and hydrology is sufficiently advanced--and information on the alluvial aquifer is adequate--to develop reasonably sound and equitable groundwater management plans. This is not to say there is no need for continuing to gather and improve the available information, only that we have sufficient information to improve management over that now being accomplished.

5. That irrigation and plant sciences are sufficiently advanced to allow approximation of optimum irrigation requirements for the various combinations of crops, soils, topography, and climatic conditions encountered in the study area.

6. That each water user is (or should be) primarily concerned with having a dependable and reasonably priced water supply which provides him with an adequate quantity and an adequate quality at the proper times at his point of use, regardless of whether it is furnished to him directly by closing down a junior right-holder or by compensation from an alternate source, such as groundwater.

7. That if it can be shown from a physical standpoint that a greater beneficial use, a better dependability of supply and an alleviation of conflicts between water users can be accomplished through planned integrated management without infringing upon vested rights, the legal problems of implementing and operating such a program can be surmounted.

From an engineering standpoint the problem is one of "systems analysis." As in any system, whether it be mechanical, electrical, or hydrogeological, it can be considered in three parts: (1) inputs and/or withdrawals of energy, matter, etc.; affecting (2) a system of interrelated and interacting elements to (3) produce responses which are of interest. In a hydrogeological system, there are inputs and withdrawals of water which vary both in time and location, and are the results of both natural and man-made conditions. The predictability of the inputs and withdrawals is dependent upon many factors and must be considered in terms of a probability based upon historical experience rather than a set figure.

The pertinent elements of the system include hydraulic and geometric characteristics of the groundwater-surface water system which affect the location and movement of water in the system. Responses of the system which are of interest include changes in groundwater levels and interchange of water between the aquifer and the stream.

GENERAL SUMMARY
OF
FINDINGS, CONCLUSIONS, AND RECOMMENDATIONS

Based upon the detailed studies which have been made during the last year under authority of Senate Bill 407, certain findings, conclusions, and recommendations stand out as being particularly pertinent. These are set forth below.

Findings

1. The average annual water supply within the South Platte River Basin is adequate to meet present requirements. However, because of the wide fluctuations in runoff, the distribution of water availability is far from satisfactory.
2. The groundwater reservoir along the main stem of the South Platte River between Denver and the State line contains approximately ten million acre-feet of water. Only a small percentage of this capacity is utilized and this only in a haphazard and unplanned way.
3. Groundwater pumping and transmountain importations have been major factors in stabilizing water supplies in the South Platte Basin. However, the pumping of groundwater has caused infringement upon prior surface water rights. Studies indicate that this infringement is not as severe as many have felt it to be.
4. The water supplies of the South Platte Basin are not being utilized or administered as efficiently and effectively as they could be.
5. Deficiencies exist in the completeness and accuracy of water use records.

Conclusions

1. Planned utilization of 10 to 15 percent of the available groundwater storage capacity in the alluvium is reasonably attainable. Use of the groundwater storage capacity can provide more efficient utilization of the total resources of the Basin, reduce shortages, and minimize conflicts between water users. This planned utilization in conjunction with surface water supplies would basically involve a heavier draft upon the groundwater supplies during low runoff years with provision for replenishment of those supplies during years of surplus runoff.

2. To achieve more optimum distribution of water supplies and accomplish desired goals, certain surface water rights should be served from groundwater sources during low runoff periods. Such operations would allow more surface water to be diverted in the upper regions, making greater re-use of return flows possible.

3. Since the groundwater in storage adjacent to the main stem of the South Platte River is currently being used to support the flowing stream, and many users are dependent upon and have rights in the return flow which joins the River via the groundwater system, provisions must be made to protect these rights and to supply them with alternate sources of water to insure the continued utilization of the groundwater supply. The cost of providing such facilities should be borne by those who benefit.

4. Optimum use of water resources within the South Platte Basin cannot be achieved without control of nonbeneficial uses or waste of water.

5. Integrated management of groundwater and surface water can be best achieved on an overall South Platte River Basin basis.

Recommendations

1. It is recommended that legislation should be passed which will allow and encourage the integrated management and administration of groundwater and surface water in the South Platte Basin. It is recommended that this be accomplished through the establishment of basin water management districts. The districts should be given specific powers to own and operate well fields, reservoirs, and other facilities.

2. It is recommended that the State Engineer be granted the authority to review and overrule the operational plans of these water management districts and any agreements which may be made. The State Engineer should continue to have the authority necessary to insure that all vested rights in the Basin are protected.

3. It is also recommended that the State Engineer should have the authority to define waste and beneficial use under the various circumstances and uses and be required to restrict diversions of water not being used beneficially. Water rights should be quantified in terms of acre-feet on the basis of beneficial use.

4. It is recommended that surface water right owners be given the opportunity to obtain alternate points of diversion at wells. Such diversions would be made under the Appropriation Doctrine.

5. It is recommended that immediate steps be taken to improve the completeness, accuracy, storage and retrieval of water measurements and records, utilizing automatic data processing methods wherever possible.

6. It is recommended that the State Engineer be granted administrative power to grant or deny changes in point of diversions, alternate points of diversion and transfers of water between uses and users, provided that investigations indicate that such changes or transfers will not materially injure the vested rights of others. Such decisions should be subject to court review.

SPECIFIC CONCLUSIONS

Each of the four reports covering the South Platte River presented conclusions, some pertaining to the particular District studied and some to the State in general. These conclusions as presented in the individual reports are contained on the following pages, along with general conclusions derived from studies of major tributaries of the South Platte as represented by Water Districts 3, 4, 5, and 6.

Water District 64

The investigations performed relative to water utilization and water availability in the Lower South Platte Valley have resulted in conclusions, some of which would apply to all river basins of the State, and others which apply primarily to the study area. The conclusions are:

1. The present utilization of Colorado's water resources is neither as efficient nor as effective as it should be.
2. Additional water is available which can be put to beneficial use. Large quantities of transient groundwater storage exist along several rivers which can be used to good advantage to help balance out seasonal surface supply variations.
3. The existing use of groundwater by well owners has many uncertain aspects which presently make these supplies undependable.
4. A continued threat exists to owners of vested surface water rights because of uncontrolled and increased well pumping.
5. Water resources and the physical mechanisms for better utilization of water resources exist, or could be constructed, which would provide for a more dependable water supply and/or increased water use.
6. Irrigation of additional lands will tend to decrease the quality of the river water downstream.

7. An opportunity exists for river basin authorities to provide more water for beneficial use, and to improve the dependability of that now being used.

The report covering Water District No. 64 also contained a proposal for increased water utilization.

Water District 8

The investigations which have been carried out in regard to the availability of water in the South Platte River have resulted in a number of basic conclusions. Some of these conclusions apply to all river basins of the State and some are related primarily to the area of study. As a result of this report, which deals with Water District No. 8, it has been concluded that:

1. The use of water in Water District No. 8 is predominantly for municipal use, particularly along the main stem of the South Platte River from which the cities of Denver, Aurora, Englewood and Littleton obtain all or a part of their municipal water supplies.

2. The use of water for irrigation along the South Platte River is diminishing as land is converted from farming to urban use.

3. Supplies from the South Platte River in Water District No. 8 are almost fully appropriated and municipalities such as Denver and Aurora must import water from the west slope to meet their increasing water needs.

4. Groundwater in storage in the alluvial aquifer of the South Platte is limited within District No. 8 and does not offer the potential for development that exists in downstream reaches of the South Platte River. The transient groundwater storage is estimated to be on the order of 30,000 acre-feet, which is relatively small in comparison to that in storage in downstream reaches of the River.

5. The groundwater alluvium does not provide a dependable source of supply for municipal use.

6. The potential exists for the development of storage and/or exchange agreements to re-regulate transmountain diversions, facilitate the re-use of return flows and for the capture and storage of flood flows; all of which can be used to effect a more efficient use of available supplies.

7. The conjunctive use of groundwater and surface water in District Nos. 1, 2, and 64 can provide for increased utilization of water in District No. 8. Return flow from increased diversions would be available downstream for direct use, for storage in reservoirs, and for recharge of groundwater aquifers. Similar increased water use could be made in the Poudre, Big Thompson, St. Vrain, Boulder Creek, and Clear Creek Basins.

8. The rapid expansion of municipal growth and corresponding municipal water use which has taken place within Water District No. 8 will occur in other areas of the State, and serves to illustrate the conditions that are encountered when urban development replaces the traditional agricultural economy.

Other conclusions which have been formulated and are applicable to all river basins of the State are given below:

1. The present utilization of Colorado's water resources is neither as efficient nor as effective as it should be.
2. Water resources and the physical mechanism for better utilization of our water resources exists or can be constructed which would provide for a more dependable water supply and/or increased water use.
3. The opportunity exists for River Basin Authorities to provide more water for beneficial use and to improve the dependability of that now being used.

In a previous report submitted to the Coordinator of Natural Resources in December, 1967, which dealt primarily with Water District No. 64, the Lower Platte River Valley from Balzac to Julesburg at the State line, seven conclusions were developed and presented. It is of interest to examine their applicability in terms of the data derived in this report for Water District No. 8. The Water District 64 conclusions are discussed in terms of the data derived from the study of Water District No. 8 in the following paragraphs:

1. The data for District No. 8 tend to reinforce the conclusion that the utilization of the State's water resources is not as efficient or as effective as it could be. The operation of District No. 8 is almost entirely for municipal use, but the administrative procedures are those developed principally for an agricultural economy. In many cases the need for cities to adhere to existing procedures governing the acquisition of water rights, changes in points of diversions, and river administration, has resulted in less than the most efficient utilization of the available water resources. Conversion of the consumptive use portion of direct flow rights to storage rights would be an example of increasing efficiency of water use, particularly advantageous to users in District No. 8.

2. There is no dependable surplus water available from the South Platte River in District No. 8. Additional water can be developed by storage such as the proposed Two Forks Project and possibly from smaller storage projects, but essentially the River is fully appropriated and used. The feasibility of storage projects such as Two Forks will be enhanced in the future as the importations of water from the west slope increase, resulting in a situation in which storage could level out imported flows and provide for more efficient use of transmountain diversions. Storage may also play a part in the utilization of return flows of transmountain water by providing opportunities for exchange. Development of storage would also provide for the capture and utilization of flood flows which now go unused.

The transient groundwater in storage in Water District No. 8, both along the South Platte and its tributaries, is limited by the shallow, narrow configuration of the alluvial valley and does not offer the potential for development that is available in downstream reaches of the river. Reducing downstream calls by managed pumping from the alluvium downstream in District Nos. 1, 2, and 64 could make more water available for District No. 8 municipal users.

3. The third conclusion is applicable to Water District No. 8 in which wells are used for municipal and irrigation supplies with the largest concentration of alluvial irrigation wells being located along Cherry Creek with smaller numbers being located along the main stem of the South Platte. The City of Littleton receives water from alluvial wells recharged by diversions from the River and from non-alluvial wells which penetrate the deeper aquifers. As previously mentioned, in June of 1968 the City imposed restrictions on the use of water for irrigation. Because groundwater does not provide a dependable source of supply adequate to meet its present and future needs, Littleton has entered into an agreement with Denver for the purchase of water under a long-term contract. The City of Englewood uses wells to meet peak period water needs, using direct-flow rights in the South Platte to more and more act as base load water supplies. Englewood's well use is uncertain and of questionable reliability.

4. In Water District No. 8 the threat to vested surface water rights does exist and must be recognized.

5. Conclusion Number 5 is equally applicable to Water District No. 8 as it is elsewhere. District No. 8 could benefit from use of wells downstream to reduce water calls.

6. In Water District No. 8 the amount of irrigated land is diminishing in the face of increased urbanization of the area surrounding metropolitan Denver and water quality in the main stem of the South Platte is affected less by irrigation than it is by the increased municipal return flows. The Metropolitan Sewer District which collects and treats sewage from many small communities which formerly returned raw or partially treated sewage to the River will have a beneficial effect on the water quality, as will the increasing pressure of Federal and State Governments for improved water pollution control measures.

7. The validity of conclusion Number 7 is substantiated by the data compiled herein on the operation of the main stem of the South Platte River in Water District No. 8. Because of its predominately municipal nature Water District No. 8 provides a case study of the problems which are encountered in areas in which operation of the River is for municipal use rather than for agriculture. District No. 8 would be a keystone in the building of a water management structure by a river basin authority charged with increasing water utilization. The foreign water imports and the storage there would provide many possibilities for exchanging on a large scale.

Water District 1

The following statements briefly summarize findings and conclusions to date:

1. The average annual historical supply of surface water available to users in Water District 1 is adequate for irrigation requirements.
2. The variability of the surface supply, ranging to less than 10 percent of the average during some months, makes sole dependence upon this source very unsatisfactory.
3. Surface storage facilities have reduced some of the uncertainty of supply by providing a better distribution of water through the season. The surface storage facilities, however, are quite inefficient, and of little value for long-term storage bridging a series of low runoff years.
4. Groundwater development and use has removed much of the uncertainty of supply for those water users fortunately situated. Subsequent exchanges and leasing of reservoir shares by ditches and individuals changing to greater groundwater use has tended to stabilize supplies even for those who have not been able to develop groundwater supplies.
5. The development of groundwater, and the subsequent exchanges and leasing of water, has come about haphazardly and without coordination on a basin basis. Although the development has improved the distribution and availability of water to most users, there has been no assurance that some parties have not been adversely affected. In addition, with little or no overall planning or coordination, the possibilities of achieving maximum beneficial use and minimum waste are nil.
6. The large alluvial aquifer underlying most of the irrigated land along the South Platte in Water District 1 can serve as a very efficient long-term storage facility with which, assuming economic feasibility, all uncertainties and inequities of supply can be virtually eliminated. The planned utilization and manipulation of groundwater storage in conjunction with surface water supplies, storage and conveyance facilities is referred to as integrated management of groundwater and surface water.
7. Full integrated management of groundwater and surface water should be planned for the entire basin, not just the area involved in this study, in order to achieve maximum benefits.
8. Full integrated management of the large and complex groundwater-surface water system of the South Platte Basin can be facilitated with computer model studies. These computer studies can help in the design and location of facilities, in the management decisions associated with operations and in determining benefits from the integrated management program.
9. Responsibilities for implementing and administering an integrated management program could probably best be handled by existing water conservancy districts. Certain problems in this regard need further study before legislation is proposed.

Water District 2

1. Water District 2 serves as a strategic link between mountain and front range tributary areas and downstream plains areas of the South Platte Basin. Because of this location, water users within Water District 2 are dependent upon inflow from several sources and at several locations. Thus, they experience quite different water supply situations within the various reaches from year to year. Urbanization is rapidly taking place in the districts above Water District 2, as well as in the upper section of Water District 2.

2. The amount of river water available for diversion under direct-flow decrees held by Water District 2 ditches has changed over the years. Some ditches in the upper portion of the Water District have experienced a reduction in diversions of direct-flow water, whereas some ditches in the lower portion have been diverting an increasing amount during recent years.

3. The amount of water remaining in storage within Water District 2 after the close of the irrigation season has been increasing over recent years, although the amount in storage at the beginning of the season does not show this trend.

4. A reservoir containing approximately 1.3 million acre-feet of groundwater underlies the main stem of the South Platte River in Water District 2. In addition, an estimated 320,000 acre-feet of groundwater underlies Beebe Draw between Barr Lake and Latham Reservoir, giving a total of some 1.6 million acre-feet of groundwater in Water District 2. During an average year less than 10 percent (120,000 to 140,000 acre-feet) of this storage capacity is actively used. During years of heavy pumping (such as 1954 and 1956) the amount withdrawn has reached 200,000 to 210,000 acre-feet within Water District 2.

5. The relationship of inflow to outflow of surface water for Water District 2 has not changed significantly on an annual basis. However, noticeable changes have occurred during certain parts of the year--particularly late summer and fall--indicating that the return flow pattern has been changing during recent years. This change started in 1953 for November and December, but not until the early 1960's during the summer months. The average annual depletion (inflow-outflow) for the Water District is about 126,000 acre-feet, some of which is transported to the Box Elder and Prospect Valleys.

6. Data and estimates of water used were obtained from a Farm Water Utilization Study prepared by the Bureau of Reclamation for the Narrows Project. The Study was for the 15-year period from 1947 to 1961, inclusive. It covered 17 of the canals which divert water for irrigation from the South Platte River in Water District 2.

7. The Bureau estimated a total of 124,635 acres as being irrigated by the 17 canals and/or by pumping from groundwater sources. Estimates from other sources show considerable discrepancy for the irrigated acreage under individual canals.

8. The estimated average annual diversion of water by the 17 canals (direct-flow plus reservoir releases) was 302,100 acre-feet. The amount diverted varied greatly from year to year. Most canals experienced a minimum diversion from the South Platte River during 1954 and 1961. Maximum diversions generally occurred during 1947 and 1952.

The estimated average annual canal loss was 84,700 acre-feet or 29 percent of the water diverted. Thus, an annual average of 217,400 acre-feet of surface water was estimated to be available at the farm headgates.

The estimated average annual amount of water pumped from groundwater sources for land under the 17 canals was estimated to be 148,600 acre-feet. Thus, the estimated total average annual supply of water at the farm headgates was 366,000 acre-feet or 2.94 acre-feet per acre. Groundwater provided about 40.6 percent of the total supply at the farm headgate.

Only a very minor amount of water was used for irrigation during the months of November, December, January, February, and March. The estimated average annual total water supply at the canal river headgates plus reservoir releases and groundwater pumped was estimated to be 450,400 acre-feet. (Some minor discrepancies will be noted in some of the above totals due to rounding of figures to the nearest 100 acre-feet).

9. The full water supply at the farm headgate was computed by the Bureau of Reclamation using (1) a combination of the Lowry-Johnson and the Thornthwaite methods to determine the consumptive use of water by crops and (2) an assumption of a 60 percent irrigation efficiency in the application of water to supply the consumptive use requirements for each of the 17 canals.

The estimated full water requirement at the farm headgate varied from 1.59 to 3.19 acre-feet per acre with an average annual headgate water requirement of 2.44 acre-feet per acre or a total of 304,200 acre-feet for the 17 canals. Monthly requirements averaged 0.08 acre-foot per acre for April, 0.14 for May, 0.47 for June, 0.66 for July, 0.60 for August, 0.36 for September, and 0.13 for October.

An assumed average of 60 percent irrigation efficiency for the combined 17 canals appears to be reasonable; however, because of different soil conditions, kinds of crops produced and methods of irrigation for each canal, it is not reasonable to expect the irrigation efficiency would be identical for each canal.

10. The canal headgate requirement includes the full requirement at the farm headgate plus canal losses. The estimated average annual requirement at the canal headgates was estimated by the Bureau of Reclamation to be 388,900 acre-feet.

11. An estimated annual average surplus of 61,500 acre-feet for the 17 canals was found as the difference between the total headgate supply and the total headgate requirement. However, 4 of the 17 canals experienced an average shortage during the 17 years and also had a shortage 50 percent of the 15-year time period. Also, many ditches experienced shortages during critical months, but showed an annual surplus because of excessive water use during other months.

The surplus would be greater than that estimated if the actual acreage irrigated were found to be less than that estimated.

If the assumed irrigation efficiency is actually less than 60 percent, the water requirements would be greater than estimated and the surplus would be less (or shortages would be greater).

Water Districts 3, 4, 5, and 6

1. The total annual supply of water available to Water District 3, 4, 5, and 6 is generally adequate for agricultural needs, although not always available at optimum times. Increasing urbanization of these areas is bringing increasing pressures on water supplies and undoubtedly will continue to do so even more in the future.

2. The natural runoff available to water users within the area under study varies considerably from year to year as influenced by widely fluctuating climatic conditions. For instance, the lowest annual natural supplies for the several water districts have been only 30 to 40 percent of the average annual values. In addition, the natural runoff pattern within each year does not match the pattern of need. The many surface storage facilities constructed by ditch and reservoir companies have greatly alleviated the latter situation by the short-term storage of surplus spring runoff for use in late summer and fall. But these, in general, are not of great value for long-term storage. In order to more fully regulate the natural runoff and provide storage to bridge a series of low-runoff years, larger and more expensive onstream reservoirs would be required. Recent studies by the U. S. Bureau of Reclamation of such possibilities in Water Districts 3, 5, and 6 have led to the conclusion that the benefits derived would not exceed the costs under present conditions.

3. Of the four water districts, only Water District 3 has a significant groundwater development. Water District 3 has approximately 900 irrigation wells, but another 700 are just outside Water District 3 in the Lone Tree and Crow Creek Valleys. The principal recharge to these 700 wells is from ditches originating within Water District 3. Less than 200 irrigation wells are located in the remaining water districts (4, 5, and 6) and are generally of rather small capacity.

4. The addition of Colorado-Big Thompson Project water has materially augmented and stabilized the total water supply of the area. This augmentation has not only been by direct use of the Project water but also indirectly through increased return flows available to lower ditches. In addition, for those water users fortunately situated over productive alluvial aquifers, groundwater has provided a stabilizing supplemental supply. Both the C-BT supplies and the groundwater supplies are especially important and valuable because (a) they are available on demand and (b) they can be called upon heavier during extended drought periods, thus tending to serve the purpose of long-term storage facilities. In addition, the C-BT Project water has been an important factor in the urban growth of these areas. If this growth would have had to rely entirely upon the transfer of agricultural water, it would have greatly affected the agricultural economy.

5. Outflow from Water Districts 3, 4, 5, and 6 has increased relative to the natural supply to the Districts, principally as a result of the addition of Colorado-Big Thompson Project water. Thus, the net effect of changes within the Districts during the past 20 years has been of benefit to downstream water users rather than a detriment. The increase in outflow is particularly significant from the Cache la Poudre and Big Thompson Basins.

6. With few exceptions, irrigation wells in Water District 3 are used to supplement surface supplies. The amount of water pumped varies inversely with the availability of surface water. Replenishment of water withdrawn occurs incidental to surface irrigation (seepage from ditches and over-irrigation) without facilities specifically constructed for this purpose. This type of "accidental" operation has been working remarkably well, but it is believed that planned utilization of the groundwater reservoir underlying parts of Water District 3 could further alleviate shortages and stabilize supplies. Such planned utilization may require an even greater amount of groundwater pumping during certain periods of time in order to reduce calls on upstream water users and/or to satisfy downstream demands. Consideration must also be given to the compensation of those who may be injured by such operations, and provisions for replenishment of groundwater during periods of favorable runoff must be made.

7. Study of diversions by ditches in Water District 3 which are heavily dependent upon return flow revealed no decline in diversions which could be attributed to increased groundwater utilization. In fact, these ditches, in general, have experienced an increased availability of water under their decrees during August and September of recent years. Many factors influence the amount of water available at a particular time and place. Besides the variable hydrologic conditions, changes in the character, pattern and efficiency of water use, importations, and groundwater utilization may all have important effects. Obviously the changes in use and importations have had a greater influence in Water District 3 than has groundwater pumping, although it should be understood that the groundwater utilization could be carried to an extreme that would adversely affect other water users.

8. As in other areas, there is a tendency to apply water in excess of crop needs during the early part of the growing season. This is water that, in some years, would be of considerably more value during July and August if it had been stored rather than used directly. At least a part of this problem is caused by outside influences, i.e., calls by downstream ditches early in the season which cut short the storage season in the upper areas.

9. Rules or agreements for operation which would be beneficial to the Water Districts under study include an agreement with water users in lower Water Districts which would allow some continuation of surface storage in the upper regions after the lower ditches go to direct irrigation and place calls against the upper districts. Such calls often result in water users applying irrigation water before needed in order to keep the water. Again, planned utilization of the groundwater reservoir to provide compensation to the downstream users may be an important part of this agreement.

10. The most important problem in need of solution within Water Districts 4, 5, and 6 is not that of groundwater-surface water integration. It is, instead, providing and planning for an orderly transfer of water from agriculture to municipal and industrial uses such that agriculture suffers a minimum in production capacity.

APPENDIX

This Appendix contains the Table of Contents and List of Tables and Figures of the individual reports. These are included to provide a ready source of reference to the substantiating material developed and presented in the separate reports covering individual water districts.

WATER DISTRICT 64

TABLE OF CONTENTS

	<u>Page</u>
LETTER OF TRANSMITTAL	
SECTION I INTRODUCTION	1
Objectives	1
Procedure.	1
SECTION II CONCLUSIONS.	2
SECTION III TENTATIVE PROPOSAL FOR INCREASED WATER UTILIZATION .	3
Summary.	3
Discussion	4
SECTION IV WATER REQUIREMENTS & SUPPLY.	9
Water Requirements	9
Water Supply	10
SECTION V DITCH & RESERVOIR SYSTEM	17
Mainstem Ditches	17
Irrigation Districts	19
SECTION VI GROUNDWATER RESOURCE & PUMPING	29
Groundwater Pumping.	29
Groundwater Resource	30
SECTION VII SOUTH PLATTE RIVER COMPACT	35
APPENDIX SECOND PROPOSAL FOR INCREASED WATER UTILIZATION.	

WATER DISTRICT 64

LIST OF TABLES AND FIGURES

	<u>Page</u>
<u>TABLES</u>	
IV-A	PRODUCTIVE ACREAGE HISTORICALLY IRRIGATED BY DITCHES & RESERVOIRS 11
IV-B	TOTAL IRRIGATION WATER REQUIREMENTS 12
IV-C	AGRICULTURAL WATER REQUIREMENTS PER ACRE. 13
IV-D	SUMMARY OF ANNUAL IRRIGATION WATER SUPPLY 1947-1966. 14
IV-E	SURFACE FLOWS AT BALZAC GAGE IN ACRE FEET 15
V-A	CANAL & RESERVOIR DECREES MAINSTEM SOUTH PLATTE RIVER. 22
V-B	GAIN IN SOUTH PLATTE RIVER FLOW 26
V-C	DIVISIONAL RIVER CALLS ORIGINATING IN W.D. 64 27
V-D	DECREES OF RESERVOIRS SERVING WATER DISTRICT 64 28
VI-A	NUMBER AND REPORTED YIELD OF IRRIGATION WELLS 31
VI-B	NUMBER AND REPORTED YIELD OF WELLS BY PERIOD. 32
VII-A	MAINSTEM CANAL AND RESERVOIR DECREES JUNIOR TO SOUTH PLATTE COMPACT 36
VII-B	DITCH DECREES SENIOR TO JUNE 14, 1897, & ADJUDICATED PRIOR TO 1923 ON TRIBUTARIES OF SOUTH PLATTE RIVER IN WATER DISTRICT 64 37
VII-C	NUMBER OF DAYS ON WHICH MEAN DAILY FLOW OF SOUTH PLATTE RIVER AT JULESBURG GAGE WAS LESS THAN 120 cfs . 38
<u>FIGURES</u>	
IV-1	SURFACE DIVERSIONS, GROUNDWATER PUMPING, AND FLOW AT BALZAC GAGE, 1947-1966 16
VI-1	ACCUMULATIVE NUMBER OF IRRIGATION WELLS 33
VI-2	ACCUMULATIVE REPORTED YIELD OF IRRIGATION WELLS 34

WATER DISTRICT 8

TABLE OF CONTENTS

	<u>Page</u>
I. CONCLUSIONS	1
II. INTRODUCTION	
Background	3
Procedure	4
Description	4
III. WATER REQUIREMENTS AND SUPPLY	
General	7
Water Use	9
Water Rights	11
Irrigation Water Requirements	18
Municipal Water Requirements	26
Groundwater	35
Surface Water Supply	42
IV. OPERATION OF WATER DISTRICT NO. 8	
Present Operation	55
Future Operation	58
Effect of District No. 8 Operation on State Line Flow	60
V. DISCUSSION	
General	64
Conclusions	65
Recommendations for Further Study	68
VI. GLOSSARY	69

WATER DISTRICT 8

LIST OF TABLES

<u>Table</u>	<u>Title</u>	<u>Page</u>
1	Adjudicated Decrees-South Platte River in District No. 8. . . .	12
2	Division Number 1 Water Calls from District No. 8 and Downstream	13
3	Monthly and Seasonal Irrigation Requirements at the Farm Headgate.	19
4	Irrigation Water Requirements at the Ditch Headgate	20
5	Recorded Diversions to the Highline Canal	21
6	Recorded Diversions to the Last Chance Ditch.	22
7	Recorded Diversions to the City Ditch	23
8	Recorded Diversions to the Nevada Ditch	24
9	Recorded Diversions to the Brown Ditch.	25
10	Annual Water Supply and Use by Denver	29
11	Annual Water Supply and Use by Aurora	30
12	Annual Water Supply and Use by Englewood.	31
13	Annual Water Supply and Use by Littleton.	32
14	Estimated Annual Yield of Denver Water Rights	33
15	Estimated Annual Yield of Aurora, Englewood and Littleton Water Rights	34
16	Summary of Wells in Water District No. 8.	35
17	Total Registered Wells in Water District No. 8.	39
18	Total Registered Alluvial Wells in Water District No. 8	40
19	Total Registered Non-Alluvial Wells in Water District No. 8	41
20	Discharge of South Platte River at South Platte, Colorado	44
21	Discharge of South Platte River at Waterton	45
22	Discharge of Plum Creek near Louviers	46

WATER DISTRICT 8

LIST OF TABLES
(cont.)

<u>Table</u>	<u>Title</u>	<u>Page</u>
23	Discharge of South Platte River at Littleton.	47
24	Discharge of Bear Creek at its Mouth.	48
25	Discharge of Cherry Creek at Denver	49
26	Discharge of South Platte River at Denver	50
27	Transmountain Diversions by Moffat Water Tunnel	51
28	Transmountain Diversions by Berthoud Pass Ditch	52
29	Transmountain Diversions by Boreas Pass Ditch	53
30	Transmountain Diversions by Harold D. Roberts Tunnel.	54
31	Population Growth in the South Platte River Basin	61

WATER DISTRICT 8

LIST OF FIGURES

<u>Figure</u>	<u>Title</u>	<u>Page</u>
1	Population Growth.	28
2	Chronological Increase in Number of Wells for Irrigation . .	37
3	Chronological Increase in Reported Yield of Wells for Irrigation.	38
4	Double-Mass Diagram, South Platte River at South Platte vs. South Platte River at Denver.	43
5	Schematic Diagram of Water District No. 8.	57
6	Double-Mass Diagram, South Platte River at Julesburg	63

WATER DISTRICT 1

TABLE OF CONTENTS

	<u>Page</u>
INTRODUCTION.	1
Area of Study.	1
Basic Premises	2
Plan of Work	3
Sources of Data.	5
STATUS OF WORK AND RESULTS TO DATE.	6
Organization, Ownership and Priorities of Ditch and Reservoir Systems, Water District 1.	6
The Riverside System.	7
The Bijou System.	10
The Fort Morgan Canal (and Jackson Lake Reservoir) System	12
The Lower Platte and Beaver System.	14
Other Systems and Facilities.	16
Summary of Priorities	16
Historic Surface Water Supplies	18
Inflow-Outflow Characteristics.	18
Fifteen-Year Study Period	22
Dependability of Surface Supply	25
Groundwater Supplies and Facilities.	26
Groundwater Storage Capacity.	26
Groundwater Development and Use	27
Water Table Fluctuations and Trends	28
Water Table Quality	29
Farm Headgate Requirements and Supply.	29
Irrigation Requirements	30
Combined Supply during Study Period	30
Operational Losses.	33
Frequency of Shortages and Surpluses.	38
Maximum Groundwater Withdrawal.	41
Modeling the System.	42
Alternative Degrees of Integrated Management	45
Alternative Number 1.	45
Alternative Number 2.	47
Alternative Number 3.	50
Thoughts on Organizational and Legislative Needs	55
Authority Needed by Management Organization or Agency.	55
The "Basin Authority"	57

WATER DISTRICT 1
TABLE OF CONTENTS (cont.)

	<u>Page</u>
SUMMARY AND CONCLUSIONS.	60
RECOMMENDATIONS FOR FUTURE WORK.	62
APPENDIX	63

WATER DISTRICT 1

LIST OF FIGURES

<u>Figure</u>		<u>Page</u>
1	Diagram of Riverside System organization and ownership.	8
2	Diagram of Bijou System organization and ownership.	11
3	Diagram of Lower Platte and Beaver System (including Jackson Lake Reservoir Co.) organization and ownership.	15
4	Farm irrigation shortages, 1947-1961. (Summation of monthly shortages within each year).	36
5	Example of cost allocation according to benefits.	54
6	Approximate boundaries of organized districts in the Plains area of the South Platte River Basin	59

WATER DISTRICT 1

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Direct flow decrees listed in geographical order, Water District 1	17
2	Direct flow decrees listed in order of priority date, Water District 1	19
3	Summary of storage decrees for reservoirs obtaining supply from the South Platte River in Water District 1	20
4	Summary of monthly discharge volumes measured at Kersey, 1917 to 1966 inclusive	23
5	Summary of monthly discharge volumes measured at Balzac, 1917 to 1966 inclusive	23
6	Comparison of parameters of 50-year and 15-year periods of record for Kersey and Balzac.	24
7	Estimated number of irrigation wells under ditches in Water District 1.	28
8	Monthly and seasonal irrigation requirements for 15-year study period as calculated by U.S.B.R.	31
9	Summary of annual canal and pump supplies compared with irrigation requirements	32
10	Farm irrigation shortages experienced during 15-year study period, annual basis. (Excess of annual irrigation requirement over annual water supply)	34
11	Farm irrigation shortages, monthly basis. (Summation of monthly shortages within each year)	35
12	Operational losses as calculated in the U.S.B.R: 15-year water utilization study: (Summation of monthly operational losses within each year). . . .	37
13	Estimated amount of groundwater withdrawn during August of 1956 under Water District 1 ditch system . .	42

WATER DISTRICT 2

TABLE OF CONTENTS

	<u>Page</u>
SUMMARY AND CONCLUSIONS	1
INTRODUCTION	
Purpose	4
Description of Area	4
References and Acknowledgements	4
Organization of Report	5
ANALYSIS AND DISCUSSION	
Evaluation of River Water Supply to Water District 2 Ditches	6
Clear Creek to Henderson	6
Henderson to St. Vrain Creek	6
St. Vrain Creek to Big Thompson River	6
Big Thompson River to Cache la Poudre River	7
Comparison of Inflows and Outflows	7
Comparison of Inflows and Computed Return Flow	8
Comparison of Inflows and Total Diversions	9
Analysis of Historic Reservoir Contents	10
Reservoirs within Water District 2	10
Reservoirs outside of Water District 2	11
Analysis of Groundwater Situation	11
Irrigation Well Registrations	12
Estimated supply, utilization and potential	12
Comparison of Diversions and Requirements	14
Estimated irrigated acreage	14
Water diverted from surface supplies and estimated total water supply from canals and pumps at farm headgates	16
Estimated canal losses	17
Estimated irrigation requirement at farm headgates	17
Estimated canal headgate requirement and total estimated supply	20
Estimated surplus or shortage of the total water supply at the canal headgate	21
ANALYSIS OF SELECTED DITCHES	
Direct Flow Decrees	23
Fulton Ditch	25
Farmers Independent Ditch	29
Union Ditch	34
SELECTED REFERENCES	39

WATER DISTRICT 2

LIST OF TABLES

<u>Table</u>		<u>Page</u>
1	Estimated Groundwater in Storage and Average Withdrawals, Water District 2.	13
2	Estimated Irrigated Acreages Served by Water District 2 Ditch Systems as Determined from Various Sources . .	14
3	Surface Water Diverted by Water District 2 Canal Systems.	15
4	Estimated Groundwater Pumped and Total Water Available at Farm Headgates, Water District 2. . . .	16
5	Estimated Average Annual Ditch Losses from Water District 2 Canal Systems	17
6	Approximate Distribution of Soil Textures under Water District 2 Canal Systems	18
7	Estimated Irrigation Requirement at Farm Headgate . . .	19
8	Monthly Water Requirements at the Farm Headgate	20
9	Estimated Canal Headgate Requirements and Total Supply Available	21
10	Estimated Annual Surpluses and Shortages at Canal Headgates.	21
11	Decreed Direct-Flow Rights from the South Platte River, Water District 2	23-24

TABLE OF CONTENTS

Data Appendix A

Water Utilization Study, Water District 2

	Page No.	Page No.
<u>Historic Inflow into W.D. 2, 1928-1966</u>		
Measured inflow above Henderson gage	1	2 - 15
Measured inflow below Henderson gage	16	17 - 30
<u>Historic Storage in Reservoirs, 1936-1967</u>		
Reservoir contents, within W.D. 2	31	32 - 44
Reservoir contents, Henrylyn Irrigation District	45	46 - 58
<u>Historic Diversions, W.D. 2, 1936-1967</u>		
BY DITCHES:		
Fulton Ditch	59	-----
Brantner Ditch	60	-----
Srighton Ditch	61	-----
Lupton Bottom Ditch	62	-----
Platteville Ditch	63	-----
Meadow Island No. 1 Ditch	64	-----
Platte Valley Ditch	65	-----
Platte Valley Ditch, Reservoir Water	66	-----
Platte Valley Ditch, C-BI Project Water	67	-----
Meadow Island No. 2 Ditch	68	-----
Farmers Independent Ditch	69	-----
Western Mutual Ditch	70	-----
Jay Thomas Ditch	71	-----
Union Ditch	72	-----
Union Ditch, Reservoir Water	73	-----
Godfrey Ditch	74	-----
Lower Latham Ditch	75	-----
Lower Latham Ditch, Reservoir Water	76	-----
Lower Latham Ditch, C-BI Project Water	77	-----
Patterson Ditch	78	-----
Plumb Ditch	79	-----
BY REACHES:		
Clear Creek to Henderson gage, direct flow*	80	81 - 92
Henderson gage to mouth of St. Vrain, direct flow	93	94 - 105
" " " " " " , reservoir water	106	107 - 113
" " " " " " , C-BI water	114	-----
" " " " " " , grand total	115	116 - 117
St. Vrain Creek to Big Thompson River, direct flow	118	119 - 128
" " " " " " , reservoir water	129	130 - 136
" " " " " " , grand total	137	138 - 139
Big Thompson River to Cache la Poudre River, dir. flow	140	141 - 150
" " " " " " , res. water	151	-----
" " " " " " , C-BI water	152	-----
" " " " " " , grand total	153	154 - 155
Clear Creek to Cache la Poudre River, direct flow	156	157 - 168
" " " " " " , reservoir water	169	170 - 176
" " " " " " , C-BI water	177	-----
" " " " " " , grand total	178	179 - 190
Comparison of Inflows vs. Outflow, by months	191-226	-----
" " " " " " , water year	227-229	-----
Comparison of Inflow vs. Diversions, by months	230-253	-----
" " " " " " , irrigation season	254-256	-----
Comparison of Inflows vs. Return flow, by months	257-292	-----
" " " " " " , water year	293-295	-----

* Also same as grand total since no reservoir or C-BI water delivered to this reach.

(Only a limited number of copies of the data appendices were printed. These are available for inspection at the Office of the State Engineer)

TABLE OF CONTENTS
 Data Appendix B - Volume I
 Water Utilization Study, Water District 2

	Prospect Valley Canal	Lower Barr Lakes	Fulton Ditch	Brantner Ditch	Brighton Canal	Lupton Bottom Ditch
Water diverted - Total	1	51	101	139	177	215
Canal losses	2	52	102	140	178	216
Surface water delivered to farm headgates	3	53	103	141	179	217
Percent of diverted water delivered to farm headgates	4	54	104	142	180	218
Groundwater pumped	5	55	105	143	181	219
Water from canals and pumps at farm headgates in acre-feet	6	56	106	144	182	220
Water from canals and pumps at farm headgates in acre-feet per acre	7	57	107	145	183	221
Frequency plots of surface water and total supply to farm headgates	8-19	58-69	108-115	146-158	184-191	222-229
Irrigation requirements at farm headgates in acre-feet	20	70	116	154	192	230
Irrigation requirements at farm headgates in acre-feet per acre	21	71	117	155	193	231
Percent of farm headgate requirement pumped	22	72	118	156	194	232
Percent of farm headgate requirement from surface water & groundwater sources	23	73	119	157	195	233
Frequency plots of total water diverted and irrigation requirements	24-35	74-85	120-127	158-165	196-203	234-241
Surplus or shortage of water at canal headgate	36	86	128	166	204	242
Frequency plots of surplus or shortage of available water at farm headgate	37-48	87-98	129-136	167-174	205-212	243-250
Total supply: Surface water diverted plus groundwater pumped	49	99	137	175	213	251
Canal headgate water requirement	50	100	138	176	214	252

(Only a limited number of copies of the data appendices were printed. These are available for inspection at the Office of the State Engineer.)

TABLE OF CONTENTS

Data Appendix B - Volume II

Water Utilization Study, Water District 2

	Page No.					
	Platteville Ditch	Meadow Island No. 1	Evans No. 2	Gillmore Ditch	Meadow Island No. 2	Farmers Independ- ent
Water diverted--Total.	253	291	329	376	413	451
Canal losses	254	292	330	377	414	452
Surface water delivered to farm headgates.	255	293	331	378	415	453
Percent of diverted water delivered to farm headgates.	256	294	332	379	416	454
Groundwater pumped	257	295	333	380	417	455
Water from canals and pumps at farms in acre-feet.	258	296	334	381	418	456
Water from canals and pumps at farms in acre-feet per acre	259	297	335	382	419	457
Frequency plots of surface water and total supply to farm headgates.	260-267	298-305	336-346	383-389	420-427	458-466
Irrigation requirements at farm headgates in acre-feet	268	306	347	390	428	467
Irrigation requirements at farm headgates in acre-feet per acre.	269	307	348	391	429	468
Percent of farm headgate requirement pumped.	270	308	349	392	430	469
Percent of farm headgate requirement from surface water & pumped water sources	271	309	350	393	431	470
Frequency plots of total water diverted and irrigation requirements.	272-279	310-317	351-361	394-401	432-439	471-479
Surplus or shortage of water at canal headgate.	280	318	362	402	440	480
Frequency plots of surplus or shortage of available water at farm headgate	281-288	319-326	363-373	403-410	441-448	481-489
Total supply: Surface water diverted plus groundwater pumped.	289	327	374	411	449	490
Canal headgate water requirement	290	328	375	412	450	491

(Only a limited number of copies of the data appendices were printed.
These are available for inspection at the Office of the State Engineer)

TABLE OF CONTENTS
 Data Appendix B - Volume III
 Water Utilization Study, Water District 2

	Page No.				
	Western Mutual Ditch	Union Ditch	Lower Latham Ditch	Patterson Ditch	Highland Ditch
Water diverted-Total.	492	530	568	606	644
Canal losses.	493	531	569	607	645
Surface water delivered to farm headgates	494	532	570	608	646
Percent of diverted water delivered to farm headgates	495	533	571	609	647
Groundwater pumped.	496	534	572	610	648
Water from canals and pumps at farms in acre-feet	497	535	573	611	649
Water from canals and pumps at farms in acre-feet per acre.	498	536	574	612	450
Frequency plots of surface water and total supply to farm headgates	499-506	537-544	575-582	613-620	651-658
Irrigation requirements at farm headgates in acre-feet.	507	545	583	621	659
Irrigation requirements at farm headgates in acre-feet per acre	508	546	584	622	660
Percent of farm headgates requirement pumped.	509	547	585	623	661
Percent of farm headgates requirement from surface water & pumped water sources	510	548	586	624	662
Frequency plots of total water diverted and irrigation requirements	511-518	549-556	587-594	625-632	663-670
Surplus or shortage of water at canal headgate.	519	557	595	633	671
Frequency plots of surplus or shortage of available water at farm headgate.	520-527	558-565	596-603	634-641	672-679
Total supply: Surface water diverted plus groundwater pumped	528	566	604	642	680
Canal headgate water requirement.	529	567	606	643	681

(Only a limited number of copies of the data appendices were printed.
 These are available for inspection at the Office of the State Engineer.)

